ViewSonic® VE510s LCD Displays

15" E²® Series Enhanced Value LCD Displays

The perfect union of style and performance.

The ViewSonic VE510s 15.0" LCD displays offer an excellent upgrade from CRTs without breaking the bank. Their elegant lines, thin bezel and 5.3cm panel add a **TOUCH OF STYLE TO YOUR DESKTOP** while taking up 75% less desk space than a CRT. These panels deliver 250 cd/m² of brightness (typ) and a high 450:1 contrast ratio (typ) to bring **SHARP IMAGES AND VIVID COLOURS TO THE SCREEN**. The fast 16ms response time delivers realistic video and crisp, scrolling text. The advanced OSD lock function preserves your settings and maintains an optimised image. Choose VE510s for performance, value and style.

Distinctive design, affordable value.

Full 15" viewable screen
Displays a full, flat 15" viewable area with crisp detail and fully saturated colour.

1024 x 768 native resolution
Excellent image detail with sharp text and graphics.

High brightness and contrast
250 cd/m² brightness (typ) and 450:1 contrast ratio (typ) for rich, detailed images.

Stylish slim-bezel design
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.

OSD/Power lock secures your settings
Prevent unauthorised changes to the menu settings. The power lock prevents the monitor from being inadvertently switched off.

OnView® controls for superior screen adjustability
Screen adjustments are precisely made via easy to use on-screen menus.

Fast 16ms LCD response time delivers superior motion images and clarity.

Integrated power supply for even greater desk-top space saving.

ViewSonic Wizard included
User-friendly Wizard software automates the setup process to deliver optimised screen performance.

Fold-up base for easy wall mounting

PC and Mac® compatible

TCO'99 and ENERGY® certified

ViewSonic®
the choice of professionals

Reliable Value

ViewSonic® VE510s LCD Displays

15" E²® Series Enhanced Value LCD Displays

1. *One-touch buttons control all major functions*
2. *Slim bezel with a 90-degree fold-up base*
3. *Space-saving design is only 5.3cm thick*
4. *Ultra compact, attractive design*

Available colour:
Silver & Black

15.0" TFT LCD DISPLAY WITH ONVIEW® CONTROLS

LCD PANEL	**Type**	15" colour TFT active matrix XGA LCD
	Display Area	30.4cm horizontal x 22.8cm vertical, 38.1cm diagonal
	Optimum Resolution	1024 x 768
	Contrast Ratio	450:1 (typ)
	Viewing Angles	120° horizontal, 100° vertical @ 10:1 160° horizontal, 135° vertical @ 5:1
	Response Time	16ms (typ)
	Colour Support	16.2M colours (6-bit + 2-bit FRC)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	250 cd/m² (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	**Analogue**	RGB analogue (75 ohms, 0.7/1.0 Vp-p)
	Frequency	F_H: 30~62kHz, F_V: 50~85Hz
	Sync	H/V separated (TTL)
COMPATIBILITY	**PC**	VGA up to 1024 x 768 non-interlaced
	Mac®[1]	Power Mac™ G3/G4 up to 1024 x 768
CONNECTOR	**Analogue**	15-pin mini D-sub
	Power	3-pin plug (CEE22)
POWER	**Voltage**	AC 100–240V, 50–60Hz (+/-3) (auto switch)
	Consumption	32W (typ), ≤ 1 watt in suspend mode
USER CONTROLS	**Basic**	Power (soft), 1, down, up, 2
	OSD	Auto Image Adjust, Brightness, Contrast, Colour Adjust [sRGB, 9300K, 6500K (default), 5400K, User Colour], Information [Mode, Model Number, Serial Number], Manual Image Adjust [H. Size, H. Position, V. Position, Fine Tune, Sharpness], Setup Menu [Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background], Memory Recall
OPERATING CONDITIONS	**Temperature**	0–40°C
	Humidity	10–90% (non-condensing)
DIMENSIONS	**Physical**	343mm (W) x 169mm (D) x 326mm (H)
WEIGHT	**Net**	3.0kg
REGULATIONS		TCO'99, ISO13046-2 (Class II), Energy®, TÜV/GS, MPRII, UL, c-UL, FCC-B, CB, CE, IC-B, EPA, NOM, VCCI, BSMI, PSB (S-Mark), C-Tick, GOST-R (PCT-BZ02), PCBC (B-mark), EMI/B, Green Mark
POWER MANAGEMENT		Meets TCO'99 and ENERGY® standards
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

ISO 9001 FM 40187
ISO 14001 EMS 40968

ViewSonic Corporation's QMS\EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

specifications

ViewSonic®
the choice of professionals

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux Tel: +32 056/85 26 27
ViewSonic Denmark Tel: +45 70 22 11 71
ViewSonic Finland Tel: +358 (0)9 5406 4070
ViewSonic Italy Tel: +34 (0) 91 63 05 339
ViewSonic MEA Tel: +971 (0) 4 88 11 871
ViewSonic Norway Tel: +47 (0) 22 88 17 60
ViewSonic Spain Tel: +34 (0) 91 63 05 339
ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

[1] Adapter may be required. Specifications subject to change without notice. Selection, offers and programmes may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. VE510s 10/05-UK

For more product information, visit us on the web at www.ViewSonicEurope.com